

Iridium 9602

The Iridium 9602 is the next generation SBD unit designed for embedded applications and is ideal for machine-to-machine (M2M) solutions.

The Iridium 9602 sends and receives packets of data over signalling channels making it suitable for integration into a variety of partner M2M solutions. It is a smaller size and form factor to its predecessor, the Iridium 9601, and includes a GPS pass-through port for connection to a GPS antenna or receiver.



The Iridium 9602 is designed to be integrated into a wireless data application with other host system hardware and software to produce a full solution designed for a specific application or vertical market. It is smaller, lighter and lower cost than its predecessor, making it ideal integration into machine-to-machine (M2M) solutions such as automatic vehicle location, asset monitoring, marine and personal tracking applications – everywhere.

How It Works

The Iridium 9602 is a single board unit designed as a ‘black box’ transceiver module with all device interfaces controlled by a single multi-pin interface connector in addition to the antenna connector.

As the product only provides the core transceiver, all other end-user field application functions such as GPS, microprocessor based logic control, digital and analog inputs, digital and analog outputs power supply and antenna must be provided by the solution developer.

The device interface across the user connector consists of a serial-data interface, DC power input, network available output and a power on/off control line. The Iridium 9602 does not incorporate nor require a Subscriber Identity Module (SIM) card to be inserted into the transceiver. The Iridium 9602 is intended to be used as a transceiver module fitted within another host system.

Features

- Single board transceiver
- Small form factor
- No SIM card
- Designed to be incorporated into an OEM solution
- RoHS compliant

Features

- Global operating capability
- Maximum mobile originated message size 340 bytes
- Maximum mobile terminated message size 270 bytes



Specifications

Dimensions 41 mm (L) x 45 mm (W) x 13 mm (D)

Weight 3 g

Operating Temperature -40°C to 85°C

Operating Humidity ≤75% RH

Storage Temperature Range -40°C to + 85°C

Storage Humidity Range ≤93% RH

Frequency Range 1616 MHz to 1626.5 MHz

Input/Output Impedance 50Ω

Multiplexing Method TDMA/FDMA

Idle Current (Average) 45mA

Idle Current (Peak) 195mA

Transmit Current (Peak) 1.5A

Transmit Current (Average) 190mA

Receive Current (Peak) 195mA

Receive Current (Average) 45m

SBD Message Transfer – Average Current 190mA

SBD Message Transfer – Average Power ≤1.0W

